

Contents

| | |
|----------|------|
| Foreword | xv |
| Preface | xvii |

PART I: INTRODUCTION TO FRACTURE MECHANICS

Chapter 1

| | |
|--|----------|
| Overview of the Problem of Fracture and Fatigue in Structures | 3 |
| 1.1 Historical Background | 3 |
| 1.2 Ductile vs. Brittle Behavior | 9 |
| 1.3 Notch Toughness | 10 |
| 1.4 Introduction to Fracture Mechanics | 14 |
| 1.4.1 Driving Force, K_I | 14 |
| 1.4.2 Resistance Force, K_c | 15 |
| 1.5 Fracture Mechanics Design | 16 |
| 1.6 Fatigue and Stress-Corrosion Crack Growth | 19 |
| 1.7 Fracture and Fatigue Control | 23 |
| 1.8 Fracture Criteria | 24 |
| 1.9 Fitness for Service | 25 |
| 1.10 Case Studies | 26 |
| 1.11 References | 26 |

Chapter 2

| | |
|---|-----------|
| Stress Analysis for Members with Cracks—K_I | 28 |
| 2.1 Introduction | 28 |
| 2.2 Stress-Concentration Factor— k_t | 29 |
| 2.3 Stress-Intensity Factor— K_I | 30 |
| 2.4 Stress-Intensity-Factor Equations | 35 |
| 2.4.1 Through-Thickness Crack | 35 |
| 2.4.2 Single-Edge Notch | 35 |

| | | |
|--------|---|----|
| 2.4.3 | Embedded Elliptical or Circular Crack in Infinite Plate | 37 |
| 2.4.4 | Surface Crack | 39 |
| 2.4.5 | Cracks Growing from Round Holes | 40 |
| 2.4.6 | Single Crack in Beam in Bending | 40 |
| 2.4.7 | Holes or Cracks Subjected to Point or Pressure Loading | 41 |
| 2.4.8 | Estimation of Other K_I Factors | 42 |
| 2.4.9 | Superposition of Stress-Intensity Factors | 47 |
| 2.5 | Crack-Tip Deformation and Plastic Zone Size | 49 |
| 2.6 | Effective K_I Factor for Large Plastic Zone Size | 51 |
| 2.7 | J_I and δ_I Driving Forces | 54 |
| 2.7.1 | J Integral | 54 |
| 2.7.2 | CTOD (δ_I) | 55 |
| 2.8 | Summary | 55 |
| 2.9 | References | 57 |
| | Appendix | 58 |
| 2.10 | Griffith, CTOD and J -Integral Theories | 58 |
| 2.10.1 | The Griffith Theory | 58 |
| 2.10.2 | Crack-Tip Opening Displacement (CTOD) and the Dugdale Model | 60 |
| 2.10.3 | J -Integral | 63 |

PART II: FRACTURE BEHAVIOR

Chapter 3

| | | |
|--|---|----|
| Resistance Forces—K_c-J_c-δ_c | 67 | |
| 3.1 | General Overview | 67 |
| 3.2 | Service Conditions Affecting Fracture Toughness | 69 |
| 3.2.1 | Temperature | 70 |
| 3.2.2 | Loading Rate | 70 |
| 3.2.3 | Constraint | 71 |
| 3.3 | ASTM Standard Fracture Tests | 76 |
| 3.4 | Fracture Behavior Regions | 79 |
| 3.5 | General ASTM Fracture Test Methodology | 80 |
| 3.5.1 | Test Specimen Size | 80 |
| 3.5.2 | Test Specimen Notch | 82 |
| 3.5.3 | Test Fixtures and Instrumentation | 82 |
| 3.5.4 | Analysis of Results | 85 |
| 3.6 | Relations Between K - J - δ | 87 |
| 3.7 | References | 90 |
| 3.8 | Appendix A: K , J , CTOD (δ) Standard Test Method—E 1820 | 91 |

| | | |
|-----|--|----|
| 3.9 | <i>Appendix B: Reference Temperature T_{ov} to Establish a Master Curve Using K_{Jc} Values in Standard Test Method E 1921</i> | 93 |
|-----|--|----|

Chapter 4

| | | |
|-----|--|-----------|
| | Effects of Temperature, Loading Rate, and Constraint | 95 |
| 4.1 | Introduction | 95 |
| 4.2 | Effects of Temperature and Loading Rate on K_{Jc} , $K_{Jc}(t)$, and K_{Id} | 96 |
| 4.3 | Effect of Loading Rate on Fracture Toughness | 98 |
| 4.4 | Effect of Constraint on Fracture Toughness | 101 |
| 4.5 | Loading-Rate Shift for Structural Steels | 109 |
| | 4.5.1 CVN Temperature Shift | 109 |
| | 4.5.2 K_{Jc} - K_{Id} Impact-Loading-Rate Shift | 110 |
| | 4.5.3 $K_{Jc}(t)$ Intermediate-Loading Rate Shift | 111 |
| | 4.5.4 Predictive Relationship for Temperature Shift | 112 |
| | 4.5.5 Significance of Temperature Shift | 112 |
| 4.6 | References | 116 |

Chapter 5

| | | |
|-----|---|------------|
| | CVN-K_{Id}-K_{Jc} Correlations | 118 |
| 5.1 | General | 118 |
| 5.2 | Two-Stage CVN- K_{Id} - K_{Jc} Correlation | 119 |
| 5.3 | K_{Jc} -CVN Upper-Shelf Correlation | 120 |
| 5.4 | K_{Id} Value at NDT Temperature | 123 |
| 5.5 | Comparison of CVN- K_{Id} - K_{Jc} - J and δ Relations | 126 |
| 5.6 | References | 131 |

Chapter 6

| | | |
|-----|---|------------|
| | Fracture-Mechanics Design | 133 |
| 6.1 | Introduction | 133 |
| 6.2 | General Fracture-Mechanics Design Procedure for Terminal Failure | 136 |
| 6.3 | Design Selection of Materials | 142 |
| 6.4 | Design Analysis of Failure of a 260-In.-Diameter Motor Case | 146 |
| 6.5 | Design Example—Selection of a High-Strength Steel for a Pressure Vessel | 150 |
| | 6.5.1 Case I—Traditional Design Approach | 150 |
| | 6.5.2 Case II—Fracture-Mechanics Design | 151 |
| | 6.5.3 General Analysis of Cases I and II | 157 |
| 6.6 | References | 159 |

PART III: FATIGUE AND ENVIRONMENTAL BEHAVIOR

| | |
|--|------------|
| <i>Chapter 7</i> | |
| Introduction to Fatigue | 163 |
| 7.1 Introduction | 163 |
| 7.2 Factors Affecting Fatigue Performance | 164 |
| 7.3 Fatigue Loading | 164 |
| 7.3.1 Constant-Amplitude Loading | 165 |
| 7.3.2 Variable-Amplitude Loading | 166 |
| 7.4 Fatigue Testing | 167 |
| 7.4.1 Small Laboratory Tests | 168 |
| 7.4.1a Fatigue-Crack-Initiation Tests | 168 |
| 7.4.1b Fatigue-Crack-Propagation Tests | 173 |
| 7.4.2 Tests of Actual or Simulated Structural Components | 174 |
| 7.5 Some Characteristics of Fatigue Cracks | 174 |
| 7.6 References | 181 |
| | |
| <i>Chapter 8</i> | |
| Fatigue-Crack Initiation | 182 |
| 8.1 General Background | 182 |
| 8.2 Effect of Stress Concentration on Fatigue-Crack Initiation | 184 |
| 8.3 Generalized Equation for Predicting the Fatigue-Crack-Initiation Threshold for Steels | 187 |
| 8.4 Methodology for Predicting Fatigue-Crack Initiation from Notches | 189 |
| 8.5 References | 192 |
| | |
| <i>Chapter 9</i> | |
| Fatigue-Crack Propagation under Constant and Variable-Amplitude Load Fluctuation | 194 |
| 9.1 General Background | 194 |
| 9.2 Fatigue-Crack-Propagation Threshold | 196 |
| 9.3 Constant Amplitude Load Fluctuation | 200 |
| 9.3.1 Martensitic Steels | 200 |
| 9.3.2 Ferrite-Pearlite Steels | 201 |
| 9.3.3 Austenitic Stainless Steels | 202 |
| 9.3.4 Aluminum and Titanium Alloys | 202 |
| 9.4 Effect of Mean Stress on Fatigue-Crack Propagation Behavior | 204 |
| 9.5 Effects on Cyclic Frequency and Waveform | 205 |

| | | |
|---------|--|-----|
| 9.6 | Effects of Stress Concentration on Fatigue-Crack Growth | 207 |
| 9.7 | Fatigue-Crack Propagation in Steel Weldments | 210 |
| 9.8 | Design Example | 212 |
| 9.9 | Variable-Amplitude Load Fluctuation | 216 |
| 9.9.1 | Probability-Density Distribution | 216 |
| 9.9.2 | Fatigue-Crack Growth under Variable-Amplitude Loading | 218 |
| 9.9.3 | Single and Multiple High-Load Fluctuations | 220 |
| 9.9.4 | Variable-Amplitude Load Fluctuations | 221 |
| 9.9.4.1 | The Root-Mean-Square (RMS) Model | 222 |
| 9.9.4.2 | Fatigue-Crack Growth Under Variable-Amplitude Ordered-Sequence Cyclic Load | 223 |
| 9.10 | Fatigue-Crack Growth in Various Steels | 225 |
| 9.11 | Fatigue-Crack Growth Under Various Unimodal Distribution Curves | 227 |
| 9.12 | References | 232 |

Chapter 10

| | | |
|-------------------|---|------------|
| Chapter 10 | Fatigue and Fracture Behavior of Welded Components | 237 |
| 10.1 | Introduction | 237 |
| 10.2 | Residual Stresses | 238 |
| 10.3 | Distortion | 240 |
| 10.4 | Stress Concentration | 241 |
| 10.5 | Weld Discontinuities and Their Effects | 243 |
| 10.5.1 | Fatigue Crack Initiation Sites | 246 |
| 10.6 | Fatigue Crack Behavior of Welded Components | 250 |
| 10.6.1 | Fatigue Behavior of Smooth Welded Components | 250 |
| 10.6.1.1 | Specimen Geometries and Test Methods | 250 |
| 10.6.1.2 | Effects of Surface Roughness | 251 |
| 10.6.2 | Fatigue Behavior of As-Welded Components | 253 |
| 10.6.2.1 | Effect of Geometry | 256 |
| 10.6.2.2 | Effect of Composition | 258 |
| 10.6.2.3 | Effect of Residual Stress | 260 |
| 10.6.2.4 | Effect of Postweld Heat Treatment | 263 |
| 10.7 | Methodologies of Various Codes and Standards | 264 |
| 10.7.1 | General | 264 |
| 10.7.2 | AASHTO Fatigue Design Curves for Welded Bridge Components | 265 |
| 10.8 | Variable Amplitude Cyclic Loads | 269 |

| | | |
|--------|--|-----|
| 10.8.1 | Example Problem | 270 |
| 10.9 | Fracture-Toughness Behavior of Welded Components | 272 |
| 10.9.1 | General Discussion | 272 |
| 10.9.2 | Weldments | 273 |
| 10.9.3 | Fracture-Toughness Tests for Weldments | 275 |
| 10.10 | References | 279 |

Chapter 11

| | | |
|-----------|--|------------|
| K_{Isc} | and Corrosion Fatigue Crack Initiation and Crack Propagation | 281 |
| 11.1 | Introduction | 281 |
| 11.2 | Stress-Corrosion Cracking | 281 |
| 11.2.1 | Fracture-Mechanics Approach | 283 |
| 11.2.2 | Experimental Procedures | 284 |
| 11.2.3 | K_{Isc} —A Material Property | 286 |
| 11.2.4 | Test Duration | 290 |
| 11.2.5 | K_{Isc} Data for Some Material-Environment Systems | 291 |
| 11.2.6 | Crack-Growth-Rate Tests | 294 |
| 11.3 | Corrosion-Fatigue Crack Initiation | 296 |
| 11.3.1 | Test Specimens and Experimental Procedures | 296 |
| 11.3.2 | Corrosion-Fatigue-Crack-Initiation Behavior of Steels | 298 |
| 11.3.2.1 | Fatigue-Crack-Initiation Behavior | 299 |
| 11.3.2.2 | Corrosion Fatigue Crack-Initiation Behavior | 299 |
| 11.3.2.3 | Effect of Cyclic-Load Frequency | 302 |
| 11.3.2.4 | Effect of Stress Ratio | 302 |
| 11.3.2.5 | Long-Life Behavior | 303 |
| 11.3.2.6 | Generalized Equation for Predicting the Corrosion-Fatigue Crack-Initiation Behavior for Steels | 304 |
| 11.4 | Corrosion-Fatigue-Crack Propagation | 305 |
| 11.4.1 | Corrosion-Fatigue Crack-Propagation Threshold | 306 |
| 11.4.2 | Corrosion-Fatigue-Crack-Propagation Behavior Below K_{Isc} | 311 |
| 11.4.3 | Effect of Cyclic-Stress Waveform | 318 |
| 11.4.4 | Environmental Effects During Transient Loading | 320 |
| 11.4.5 | Generalized Corrosion-Fatigue Behavior | 322 |
| 11.5 | Prevention of Corrosion-Fatigue Failures | 325 |
| 11.6 | References | 326 |

PART IV: FRACTURE AND FATIGUE CONTROL

| | |
|---|------------|
| <i>Chapter 12</i> | |
| Fracture and Fatigue Control | 333 |
| 12.1 Introduction | 333 |
| 12.2 Historical Background | 337 |
| 12.3 Fracture and Fatigue Control Plan | 339 |
| 12.3.1 Identification of the Factors | 340 |
| 12.3.2 Establishment of the Relative Contribution | 342 |
| 12.3.3 Determination of Relative Efficiency | 346 |
| 12.3.4 Recommendation of Specific Design Considerations | 353 |
| 12.4 Fracture Control Plan for Steel Bridges | 354 |
| 12.4.1 General | 354 |
| 12.4.2 Design | 354 |
| 12.4.3 Fabrication | 355 |
| 12.4.4 Material | 355 |
| 12.4.5 AASHTO Charpy V-Notch Requirements | 356 |
| 12.4.6 Verification of the AASHTO Fracture Toughness Requirement | 357 |
| 12.4.7 High-Performance Steels | 357 |
| 12.5 Comprehensive Fracture-Control Plans— George R. Irwin | 357 |
| 12.6 References | 363 |
| <i>Chapter 13</i> | |
| Fracture Criteria | 364 |
| 13.1 Introduction | 364 |
| 13.2 General Levels of Performance | 366 |
| 13.3 Consequences of Failure | 368 |
| 13.4 Original 15-ft-lb CVN Impact Criterion for Ship Steels | 370 |
| 13.5 Transition-Temperature Criterion | 373 |
| 13.6 Through-Thickness Yielding Criterion | 374 |
| 13.7 Leak-Before-Break Criterion | 378 |
| 13.8 Fracture Criterion for Steel Bridges | 381 |
| 13.9 Summary | 382 |
| 13.10 References | 382 |
| <i>Chapter 14</i> | |
| Fitness for Service | 384 |

| | | |
|--------|--|-----|
| 14.1 | Introduction | 384 |
| 14.2 | Use of Fracture Mechanics in Fitness-for-Service Analysis | 385 |
| 14.2.1 | General | 385 |
| 14.2.2 | Effect of Loading Rate | 386 |
| 14.2.3 | Effect of Constraint | 389 |
| 14.2.4 | Effect of Many Factors | 394 |
| 14.3 | Existing Fitness-for-Service Procedures | 396 |
| 14.3.1 | General | 396 |
| 14.3.2 | PD 6493 | 397 |
| 14.3.3 | ASME Section XI | 401 |
| 14.3.4 | API 579 | 402 |
| 14.4 | Benefits of a Proof or Hydro-Test to Establish Fitness for Continued Service | 402 |
| 14.5 | Difference Between Initiation and Arrest (Propagation) Fracture Toughness Behavior | 404 |
| 14.6 | References | 408 |

PART V: APPLICATIONS OF FRACTURE MECHANICS—CASE STUDIES

Chapter 15

| | | |
|---|--|-----|
| Importance of Fracture Toughness and Proper Fabrication Procedures—The Bryte Bend Bridge | 413 | |
| 15.1 | Introduction | 413 |
| 15.2 | AASHTO Fracture Control Plan for Steel Bridges | 414 |
| 15.3 | Bryte Bend Bridge Brittle Fracture | 414 |
| 15.4 | Design Aspects of the Bryte Bend Bridge as Related to the AASHTO Fracture Control Plan (FCP) | 420 |
| 15.5 | Adequacy of the Current AASHTO Fracture Control Plan | 423 |
| 15.5.1 | Implied vs. Guaranteed Notch Toughness | 423 |
| 15.5.2 | Effect of Details on Fatigue Life | 424 |
| 15.5.3 | Summary | 426 |
| 15.6 | References | 427 |

Chapter 16

| | | |
|--|---|-----|
| Importance of Constraint and Loading—The Ingram Barge | 428 | |
| 16.1 | Introduction | 428 |
| 16.2 | Effect of Constraint on Structural Behavior | 428 |
| 16.3 | Constraint Experiences in the Ship Industry | 431 |
| 16.4 | Ingram Barge Failure | 431 |
| 16.5 | Summary | 436 |
| 16.6 | References | 437 |

Chapter 17

| | |
|---|------------|
| Importance of Loading and Inspection—Trans Alaska Pipeline Service Oil Tankers | 438 |
| 17.1 Introduction | 438 |
| 17.2 Background | 439 |
| 17.3 Fracture Mechanics Methodology | 439 |
| 17.4 Application of Methodology to a Detail in an Oil Tanker | 441 |
| 17.4.1 Identification of Critical Details | 441 |
| 17.4.2 Fracture Toughness | 441 |
| 17.4.3 Stress Intensity Factors and Critical Crack Size for Critical Details | 443 |
| 17.4.4 Inspection Capability for Initial Crack Size, a_0 | 444 |
| 17.4.5 Determination of Histogram for Fatigue Loading | 445 |
| 17.4.6 Fatigue Crack Propagation in Bottom Shell Plates | 447 |
| 17.5 Effect of Reduced Fatigue Loading | 450 |
| 17.6 Summary | 453 |
| 17.7 References | 454 |

Chapter 18

| | |
|---|------------|
| Importance of Proper Analysis, Fracture Toughness, Fabrication, and Loading on Structural Behavior—Failure Analysis of a Lock-and-Dam Sheet Piling | 455 |
| 18.1 Introduction | 455 |
| 18.2 Description of the Failure | 457 |
| 18.3 Steel Properties | 457 |
| 18.4 Failure Analysis of Sheet 55 | 462 |
| 18.5 Summary | 466 |
| 18.6 References | 467 |

Chapter 19

| | |
|--|------------|
| Importance of Loading Rate on Structural Performance—Burst Tests of Steel Casings | 468 |
| 19.1 Introduction | 468 |
| 19.2 Material and Experimental Procedures | 468 |
| 19.3 Experimental Procedure | 469 |
| 19.4 Failure Analysis | 472 |
| 19.5 Metallographic Analysis | 476 |
| 19.6 Examination of API Specifications for J-55 and K-55 Casing | 482 |
| 19.7 References | 487 |

| | |
|-------------------|------------|
| <i>Chapter 20</i> | |
| Problems | 491 |
| Part I | 491 |
| Part II | 494 |
| Part III | 499 |
| Part IV | 502 |
| | |
| <i>Index</i> | 507 |