

DIN EN 13384-2:2015-06 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 2: Chimneys serving more than one heating appliance

Contents

Page

Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	8
4 General symbols and abbreviations	9
5 Calculation method	9
5.1 General principles	9
5.2 Pressure equilibrium condition	11
5.2.1 Negative pressure chimneys	11
5.2.2 Positive pressure chimneys	12
5.3 Mass flow requirement	13
5.4 Pressure requirements	13
5.4.1 Negative pressure chimneys	13
5.4.2 Positive pressure chimneys	14
5.5 Temperature requirement	15
5.6 Calculation procedure	15
6 Flue gas data characterising the heating appliance	18
7 Data for chimney and connecting flue pipes	19
8 Basic data for the calculation	20
8.1 General	20
8.2 Air temperatures	20
8.2.1 External air temperature (TL)	20
8.2.2 Ambient air temperature (Tu)	20
8.3 External air pressure (pL)	20
8.4 Gas constant	20
8.4.1 Gas constant of the air (RL)	20
8.4.2 Gas constant of flue gas (R)	20
8.5 Density of air (L)	20
8.6 Specific heat capacity of the flue gas (cp)	20
8.7 Water vapour content ((H2O),j) and condensing temperature (Tsp)	20
8.8 Correction factor for temperature instability (SH)	21
8.9 Flow safety coefficient (SE)	21
8.10 External coefficient of heat transfer	21
9 Determination of temperatures	21
10 Mixing calculations	23
10.1 General	23
10.2 Flue gas mass flow (j,m)	23
10.3 Flue gas temperature at the inlet of the chimney segment (Te,j)	23
10.4 CO2-content of the flue gas in the chimney segment ((CO2),j)	23

10.5	H ₂ O-content of the flue gas ((H ₂ O) _j)	24
10.6	Gas constant of the flue gas (R _j)	24
10.7	Flue gas data	24
10.7.1	Specific heat capacity (cpV _j), (cp _j)	24
10.7.2	Thermal conductivity of the flue gas (AV _j), (A _j)	24
10.7.3	Dynamic viscosity (AV _j), (A _j)	25
10.7.4	Condensing temperature (TSP)	25
11	Density and velocity of the flue gas	25
12	Determination of the pressures	26
12.1	Pressures at each inlet of the chimney segments	26
12.1.1	Draught	26
12.1.2	Positive pressure	26
12.1.3	Draught due to chimney effect in the chimney segment (PH _j)	27
12.1.4	Pressure resistance in the chimney segment (PR _j)	27
12.2	Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin)	29
12.2.1	Minimum required and maximum allowed draught	29
12.2.2	Maximum available and minimum allowed differential pressure	29
12.2.3	Calculated pressure resistance of the connecting flue pipe (PV _j)	30
12.2.4	Calculated pressure resistance of the air supply (PBc _j)	32
13	Inner wall temperature	33
14	Cascade installations	33
14.1	Principle of the calculation method	33
14.2	Pressure equilibrium condition	34
14.2.1	Negative pressure cascade installation	34
14.2.2	Positive pressure cascade installation	35
14.3	Mass flow requirement	36
14.4	Pressure requirements	36
14.4.1	Negative pressure chimneys	36
14.4.2	Positive pressure chimneys	37
14.5	Temperature requirement	38
14.6	Calculation procedure	38
14.7	Pressures at the outlet of the connecting flue pipe and pressures at the inlet of the collector segment	38
14.7.1	Pressure at the flue gas inlet into the collector segment (PZC _{j,l} or PZOC _{j,l})	38
14.7.2	Pressures required or available at the outlet of the connecting flue pipe (PZeC _{j,l} , PZOeC _{j,l})	42
14.8	Inner wall temperature (TiobC _{j,l})	44
15	Balanced flue chimney	44
15.1	Principle of the calculation method	44
15.2	Pressure equilibrium condition	44
15.3	Mass flow requirement	45
15.4	Pressure requirements	45
15.4.1	Negative pressure chimneys	45
15.4.2	Positive pressure chimneys	45
15.5	Temperature requirements	47
15.6	Calculation procedure for balanced flue chimneys	47
15.7	Mass flow of the supply air	49
15.8	Determination of the temperatures in balanced flue chimneys	50
15.8.1	Separate ducts	50
15.8.2	Concentric ducts	50
15.8.3	Concentric connection pipes	58
15.9	Pressures of the air supply ducts	64
15.9.1	Draught due to chimney effect of the air supply duct of chimney segment j	64
15.9.2	Draught due to chimney effect of the air supply duct of connection pipes	64
15.9.3	Pressure resistance of the air supply duct of the chimney segment j (PRB _j)	64

15.9.4	Pressure resistance of the air supply duct of the connection pipe j (PRBV,j)	66
15.10	Density and velocity of the supply air	68
15.10.1	Density and velocity of the supply air in the air supply duct averaged over the length of the chimney segment	68
15.10.2	Density and velocity of the supply air averaged over the length of the connection pipes	68
16	Consideration of chimney fans	69
16.1	General	69
16.2	Inline fans	70
16.3	Exhaust fans	71
Annex A (informative) Recommendations		72
A.1	General	72
A.2	Recommendations for the chimney and heating appliances	72
A.3	Recommendations for connecting flue pipes	72
Annex B (informative) Characteristics for the heating appliance		73