

DIN EN 12977-2:2012-06 (E)

Thermal solar systems and components - Custom built systems - Part 2: Test methods for solar water heaters and combisystems

Contents	Page
Foreword	4
Introduction	5
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 Symbols and abbreviations	10
5 System classification	12
6 Test methods	12
6.1 Introduction	12
6.2 General	12
6.3 Materials	13
6.4 Components and pipework	13
6.5 Safety equipment and indicators	15
6.6 Installation	16
6.7 Initial operation, inspection and commissioning	16
6.8 Documentation	17
6.9 System performance (for small systems only)	17
6.10 Water wastage (for small systems only)	17
7 Optional performance test of small custom built solar heating systems	17
7.1 General	17
7.2 Test of the solar collector	18
7.3 Test of the water store(s)	18
7.4 Test of the control equipment	18
7.5 Determination of the hot water comfort	18
7.6 System simulation model	19
7.7 Long-term performance prediction	19
7.8 Presentation of performance indicators	25
8 Performance test report	26
Annex A (normative) Reference conditions for performance prediction	28
A.1 General	28
A.2 Pipe diameter and insulation thickness	30
A.3 Calculation of mains water temperature at reference location	30
A.4 Space heating load	31
Annex B (normative) Additional information regarding the calculation of the fractional energy savings	37
B.1 Definition of a conventional reference water heating system	37
B.2 Calculation of fractional energy savings for other conditions	37

Annex C (informative) Short-term system testing	39
C.1 General	39
C.2 Instrumentation, data acquisition and processing	39
C.3 Check of short-term system performance	41
C.4 Short-term test for long-term system performance prediction	44
Annex D (informative) Long-term monitoring	51
D.1 General	51
D.2 Evaluation chart	52
D.3 Monitoring equipment	52
D.4 Data analysis	52
Annex E (informative) Determination of water wastage	53
Bibliography	54
Figures Figure 1 -- Energy balance for one-store and two-store solar-plus-supplementary systems	21
Figure 2 -- Comparison of the gross auxiliary energy demand of the solar heating system, Q_{aux}, to the gross energy demand of the conventional heating system, Q_{conv}	22
Figure 3 -- Energy balance for solar only systems	24
Figure 4 -- Energy balance for solar preheat systems	25
Figure C.1 -- Principle of the short term system performance check: Check and intercomparison of useful energy gain	41
Figure C.2 -- Principle of the short-term test and of the subsequent long term system performance prediction	45
Figure C.3 -- Example of the predicted performance dependence on load level and irradiation for a solar domestic hot water heating system (see [8])	50
Tables Table 1 -- Division for factory made and custom built solar heating systems	6
Table 2 -- Symbols, definition and unit (1 of 2)	10
Table 2 -- Symbols, definition and unit (2 of 2)	11
Table 3 -- Presentation of system performance indicators for solar-plus-supplementary systems ...	26
Table 4 -- Presentation of system performance indicators for solar-only and solar preheat systems	26
Table A.1 -- Reference conditions for performance presentation (1 of 2)	28
Table A.1 -- Reference conditions for performance presentation (2 of 2)	29
Table A.2 -- External pipe diameter and insulation thickness for forced-circulation systems	30
Table A.3 -- Data for calculation of the mains water temperature at the reference locations	31
Table A.4 -- Space heating load file for Stockholm	32
Table A.5 -- Space heating load file for Davos	33
Table A.6 -- Space heating load file for Würzburg (1 of 2)	34
Table A.6 -- Space heating load file for Würzburg (2 of 2)	35

Table A.7 -- Space heating load file for Athens - Example to be updated	36
Table C.1 -- Variables to be measured and corresponding maximum sampling intervals	43
Table C.2 -- Variables to be measured during system test, and corresponding maximum sampling intervals	46
Table C.3 -- Range of variations of the driving variables to be scanned during a test outdoors	47
Table C.4 -- Permissible standard deviation for secondary collector parameters	49